LUXLAY

VINYL PLANKS

ANTI-BACTERIAL PU COATING

228.6 x 1219.2mm

UNDERFOOT COMFORT

2.787m² PER BOX

0.5mm WEAR LAYER

25 YEAR DOMESTIC WARRANTY

5mm THICKNESS

10 YEAR COMMERCIAL WARRANTY

LUXLAY

VINYL PLANKS

Luxlay is at the forefront of technology for Modular Flooring. The 5mm thickness gives superior all-round comfort and reduces noise transfer levels.

SPOTTED GUM - LL3505

MARRI - LL3506

HICKORY GREY - LL3509

IRON BARK - LL3510

VICTORIAN OAK - LL3507

MAPLETON OAK - LL3508

EBONY ASH - LL3511

ALPINE OAK - LL3512

FEATURES & BENEFITS:

- Reinforced fibreglass core for unparalleled stability
- Aesthetic timbers sourced locally and internationally
- Easy lay technology perfect for DIY
- 5.0mm thickness for extra underfoot comfort and acoustics
- 0.5mm wear layer for long lasting durability, ideal for children and pets
- Commercial wear layer allows LuxLay to be installed in most circumstances

LUXLAY

VINYL PLANKS

CHARACTERISTICS	STANDARD	RESULT
Dimensions	-	228.6x1219.2mm
Thickness	-	5mm
Wear Layer	-	0.5mm
Anti-Bacterial Test (ATCC 8739 & ATCC 6538)	ASTM E2180-07	99.99% Reduction
Dimensional Stability	ASTM F2199-09	Pass
Formaldehyde Content	ASTM D6007-14	ND
Resistance to Heat	ASTM F1514-03	Pass
VOC Emissions	CDPH/EHLB 01350	Pass
Wet Pendulum Slip Resistance	AS 4586	P2
Domestic Warranty	-	25 Years
Commercial Warranty	-	10 Years

LUX LAY

METWEST BUILDING SUPPLIES

www.metwestbuildingsupplies.com.au